

pojlock  
Lifts

# 2m Independence Steplift

*reaching new heights in elegant access solutions*



# 2m Independence Steplift

*reaching new heights in elegant access solutions*

The access solution that takes you further, the new Independence Steplift model raises the user up to a maximum 2 metres while continuing to provide the strength, modern aesthetics and configuration options you expect from Pollock Lifts.

## 3 PLATFORM SIZES

### 800W

PLATFORM: 800 x 1400mm  
FOOTPRINT: 1110 x 1660mm  
GATE CLEARWAY: 800mm

### 900W

PLATFORM: 900 x 1400mm  
FOOTPRINT: 1210 x 1660mm  
GATE CLEARWAY: 900mm

### 1100W

PLATFORM: 1100 x 1400mm  
FOOTPRINT: 1410 x 1660mm  
GATE CLEARWAY: 1100mm

## KEY FEATURES AND BENEFITS

- > Travel up to 2m
- > Maximum capacity of 500kg
- > Modern lightweight design
- > Suitable for internal or external use (corrosion resistant)
- > Modular Aluminium construction
- > Stylish side panels and upper / lower gates in powder coated aluminium with Acrylic infills
- > Gates can be rehanded (opening direction changed) on site to suit
- > Simple to install and easy to service
- > 2-piece system
- > Integral pump - no need for remote pump unit minimising installation time
- > Battery powered (power pack integral to rail structure)
- > Can be reinstalled to a new location

## Safety Features

- > On board manual lowering system
- > Emergency release on upper and lower level gates
- > Auto reverse on upper and lower level gates
- > Full platform safety edge as standard



### Optional Features

- > 3 platform sizes
- > Automatic upper level gate\*
- > Automatic lower level gate\*  
\*mechanism can be rehanded on site if required
- > Upgradable post installation to add automatic gates at a later date
- > Post mounted call station
- > Configurable control side
- > Tactile controls - braille buttons
- > Light curtain
- > Optional RAL colours

### Specification

- > Easy access set-up switches
- > Drive: Direct acting hydraulic
- > Rated Speed: 0.1 meters per second
- > Power supply electrical requirements:  
220/240-50/60 Hz - 13A single phase (max)  
Dedicated RCD protected supply
- > Control system: Low voltage 24VDC
- > Operating temperature range: -10 to +40
- > Compliance standards:  
BS8300 & ISO9386-1 Machinery Directive 98/37/EC

Models	Platform Size	Footprint Required	Gate Clearway
800W	800 x 1400	1110 x 1660	800
900W	900 x 1400	1210 x 1660	900
1100W	1100 x 1400	1410 x 1660	1100

All measurements are in millimetres (mm)

NOTE: Photographs are for guidance only.  
Lift style and finishes are dependant on model and optional features selected.





## Also from Pollock Lifts...



### Independence Steplift Range

*...the next generation in 1 metre step lift access*



### Through-floor Lift Range

*...elevating excellence with a modern and unobtrusive 2 floor access solution*



### Disabled Access Range

*...offering freedom in any environment with multi-level access lifts*

#### For further information contact Pollock Lifts:

Unit 1 Sloefield Drive, Trooperslane Industrial Estate,  
Carrickfergus, Co. Antrim BT38 8GX

Tel: +44 (0) 28 9336 8167

Email: [info@pollocklifts.co.uk](mailto:info@pollocklifts.co.uk)

[www.pollocklifts.co.uk](http://www.pollocklifts.co.uk)

NOTE: Specification is correct at time of print and is subject to change as part of our ongoing Research and Development programme.